



DECLARATION OF PERFORMANCE VEDAFEU C No. C-22/0321

According to Annex III of the regulation EU No. 305/2011

- Product name:** Firestop ropes VEDAFEU C with diameters from 12 to 180 mm.
VEDAFEU C12, VEDAFEU C20, VEDAFEU C30, VEDAFEU C40, VEDAFEU C50,
VEDAFEU C60, VEDAFEU C75, VEDAFEU C90, VEDAFEU C105, VEDAFEU
C120, VEDAFEU C135, VEDAFEU C150, VEDAFEU C165, VEDAFEU C180.
- Expected Usage:** Fire compartmentation and/or fire protection for linear joint seals
horizontal and vertical with static or dynamic elements.
- Manufacturer:** GV2 VEDA FRANCE
CS63052
95972 – ROISSY CDG CEDEX
T: +33 1 48 61 60 80
E: contact@vedafrance.com
W: www.vedafrance.com
- AVCP System:** Assessment and Verification of Constancy and Performance: System 1
- Documents:** European Assessment Document: EAD 350141-00-1106 (2017)
European Technical Assessment: ETA-22/0321 of 31st December 2022

Technical Assessment Body:

TZUS, Prosecká 811/76a, 190 00 Praha, Czech Republic (TAB No. 1020)

Certificate of Product Constancy: 1812-CPR-2062

Notify bodies: EFECTIS France (NB. No. 1812) Route de l'Orme des
Merisiers, 91193 SAINT AUBIN France



VEDA TECHNIK
Joints de dilatation - Systèmes coupe-feu est une marque de GV2 - VEDA FRANCE



GV2 - VEDA FRANCE

20, Allée des Erables - Bât. E - 93420 Villepinte - France

Adresse Postale

CS 63052 - 95972 Roissy CDG Cedex

SAS au capital de 603 500 € - RCS Bobigny 439 138 355 - Siret n°439 138 355 000 45 - N° TVA : FR 71 439 138 355

Tél : + 33 (0)1 48 61 70 80

Fax : + 33 (0)1 48 61 70 81

E-mail : contact@vedafrance.com

Web : www.vedafrance.com - www.vedatechnik.com

6. Declared Performance:


Product dimensions:	Ø12 to Ø180 mm
Joint gap:	From 10 mm to 150 mm (ETA Annex 1)
Supports:	Reinforced concrete structure (≥ 2200 kg/m ³) Aerated concrete blocks (≥ 500 kg/m ³)
Reaction to fire:	A1
Fire resistance:	From EI 120 to EI 240 (ETA Annex 2)
Durability:	Y1
Airborne Sound	Rs,w (C; Ctr) = 34 (-1; -2) dB ¹⁾
Insulation:	Rs,w (C; Ctr) = 36 (0; -2) dB ²⁾
	Rs,w (C; Ctr) = 40 (-1; -3) dB ³⁾
	Rs,w (C; Ctr) = 44 (-1; -4) dB ^{4), 5)}
	¹⁾ VEDAFEU C single joint ø 30 mm for 20 mm gap
	²⁾ VEDAFEU C single joint ø 60 mm for 40 mm gap
	³⁾ VEDAFEU C single joint ø 90 mm for 60 mm gap
	⁴⁾ VEDAFEU C double joint ø 30 mm for 20 mm gap
	⁵⁾ VEDAFEU C double joint ø 60 mm for 40 mm gap

7. Specific Technical Documentation:

The performance of the product identified above is in conformity with the set of declared performances.

This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above (See article 3).

Signed for and on behalf of the manufacturer by:



Loïc Randé

Technical Director

Villepinte, 04/01/2023